



AUTHORIZED DISTRIBUTOR

## Mô-đun đo độ ẩm và nhiệt độ Vaisala HUMICAP® HMM170

		HMM170	1	2	3	4	5	6	7	8	PRICE
<b>Humidity Module</b>											
<b>1 Output signals</b>	<b>RS485 digital output only (Modbus RTU / RS485 in use)</b>		1								
	4... 20 mA (3.6 mA when in error state)		2								
Digital output always included	4... 20 mA (21 mA when in error state)		3								
	0... 20 mA (21 mA when in error state)		4								
	0... 10 V (10.3 V when in error state)		5								
analog outputs can always be activated and reconfigured afterwards	0... 5 V (5.5 V when in error state)		6								
	1... 5 V (5.5 V when in error state)		7								
	0... 1 V (1.1 V when in error state)		8								
				Channel 1	Channel 2	Channel 3					
				↓	↓	↓					
<b>2 Parameter and scaling</b>	<b>No analog output (select 'AAA' if only digital output is wished)</b>			A	A	A					
<b>3 for analog output</b>	<b>Td/f with warmed probe default*</b>	0... +100 °C (+32... +212 °F)		B	B	B					
<b>4 channels 1, 2, 3</b>	<b>Td/f with warmed probe default*</b>	-20...+100 °C (-4...+212 °F)		C	C	C					
	<b>Dewpoint/frostpoint (Td/f) output</b>	0... +100 °C (+32... +212 °F)		D	D	D					
	<b>Relative Humidity (RH)</b>	0... 100 % RH		E	E	E					
	<b>T</b>	0... +180 °C (+32... +356 °F)		F	F	F					
	<b>T</b>	-70... +180 °C (-94... +356 °F)		G	G	G					
	<b>T</b>	0... +100 °C (+32... +212 °F)		H	H	H					
<i>CUSTOMER FREE SCALE</i>	<i>Td/f (between -80... +100 °C, metric)</i>	Scale: _____		J	J	J					
	<i>T (between -100... +200 °C, metric)</i>	Scale: _____		K	K	K					
	<i>Td/f (between -120... +212 °F, non-metric)</i>	Scale: _____		L	L	L					
	<i>T (between -148... 392 °F, non-metric)</i>	Scale: _____		M	M	M					
	For moisture in oil <b>Water activity (aw)</b>	0... 1		R	R	R					
	For moisture in oil <b>Relative saturation (% RS)</b>	0... 100 % RS		S	S	S					
	Mineral transformer oil only <b>PPM<sub>weight</sub></b>	0...100 ppm		T	T	T					
<i>CUSTOMER FREE SCALE</i>	<i>PPM<sub>volume</sub></i>	Scale: _____ (0... 10 <sup>7</sup> ppm)		X	X	X					
	<i>Mixing ratio (x)</i>	Scale: _____ (0... 10 <sup>3</sup> g/kg)		Y	Y	Y					
	<i>Absolute humidity</i>	Scale: _____ (0... 10 <sup>3</sup> g/m <sup>3</sup> )		Z	Z	Z					
<b>*NOTE: When warmed probe is enabled, only dew/frost point (Td/f) output is possible. This prevents erroneous RH and T outputs. Probe warming can be manually set on/off afterwards.</b>											
<b>5 Probe type and cable length</b>	<b>Stainless steel probe with 2 m / 6.5 ft cable (-70 °C... +180 °C)</b>										1
	<i>Stainless steel probe with 5 m / 16.4 ft cable (-70 °C... +180 °C)</i>										2
	<i>Stainless steel probe with 10 m / 32.8 ft cable (-70 °C... +180 °C)</i>										3
<b>6 Humidity sensor type and chemical purge</b>	<b>Purge on every start-up and after every 24 hours</b>	<b>HUMICAP® R2C</b>									A
	<b>Purge on every start-up only</b>	<b>HUMICAP® R2C</b>									B
	<b>No purge (manual purge is still possible)</b>	<b>HUMICAP® R2C</b>									C
	<b>Moisture in oil sensor</b>	<b>HUMICAP® 180L2</b>									D
	<i>H<sub>2</sub>O<sub>2</sub> tolerant sensor with start-up and 24h purge</i>	<i>HUMICAP® 180VC</i>									E
<b>7 Sensor protection</b>	<b>PPS with stainless steel mesh (general purpose)</b>	<i>(spare: DRW010281SP)</i>									1
	<b>Sintered stainless steel filter with 38 um pore size</b>	<i>(spare: HM47280SP)</i>									2
	<b>Sintered PTFE filter with 20 um pore size</b>	<i>(spare: 219452SP)</i>									3
	<b>Stainless steel filter for moisture in oil and vacuum</b>	<i>(spare: HM47453SP)</i>									4
<b>8 Product identity</b>	<b>Vaisala (default)</b>										A
										TOTAL	
										QTY	
										TOTAL VALUE	

Selections in bold are included in the prices of the basic versions.  
Selections in italic are available at an extra price.

Example of order code with typical settings for RH&T measurement: **HMM170 2 E G A 1 A 1 A**  
 Example of order code with typical settings for dew point measurement: **HMM170 2 C C C 1 A 1 A**  
 Example of order code with typical settings for moisture in oil measurement: **HMM170 2 J K L 1 D 4 A**

End customer: \_\_\_\_\_

**Accessories:**

- 219690 USB cable for PC connection
- 219980 HM70 Hand-held connection cable
- HMP247CG Feedthrough
- SWG12NPT12 Swagelok NPT1/2" Pressure-tight Installation Adapter for Probe
- SWG12ISO12 Swagelok ISO 1/2" Pressure-tight Installation Adapter for Probe
- 210697 Duct installation kit for probe
- 226067 Probe Mounting Clamp Set (10 pcs)

**Spare parts:**

- DRW010281SP PPS Plastic grid & stainless steel netting
- HM47280SP Stainless steel sintered filter
- 219452SP Sintered PTFE filter with 20 um pore size
- HM47453SP Stainless steel filter for moisture in oil and vacuum



AUTHORIZED DISTRIBUTOR

**ANS VIETNAM (Anh Nghi Son Service Trading Co., Ltd.)**

Add: D3, KDC Mieu Noi, Dinh Tien Hoang St., W.3, Binh Thanh Dist., HCMC, Vietnam

Tel: 028 3517 0401 - 028 3517 0402 - Fax: 028 3517 0403

Phone: 0908016350

Email: [sales@ansvietnam.com](mailto:sales@ansvietnam.com) / [trang.ans@ansvietnam.com](mailto:trang.ans@ansvietnam.com)

Website <http://vaisala.ansvietnam.com/>